

# ***ROAD TECH***

## **10MM SOFT SHACKLE**

**MXE425**

### **INSTRUCTIONS**

**ALWAYS KEEP WITH THE SHACKLE - DO NOT DISCARD**

#### **INSTRUCTIONS FOR USE:**

1. Inspect shackle for wear and tear
2. Loosen loop to open
3. Attach to rated recovery point
  - a. Either threading eye end of shackle through recovery point
  - b. Creating a loop around recovery hook
4. Connect to recovery strap by passing soft shackle loop through recovery strap loop
5. Pass knot on soft shackle through soft shackle loop to create connection
6. Remove shackle and inspect for damage
7. Store in a dry, dark place

#### **READ BEFORE USE**

#### **SOFT SHACKLES ARE GENERALLY SAFER WHEN USED IN RECOVERY SITUATIONS AS LONG AS THE BELOW IS ADHERED TO:**

- Wear can cause a reduction in rated capacity. Always check for cuts, nicks, and abrasions before use. Shackles with wear should be removed from service/use
- Use only with a rated recovery point, do not use vehicle tow ball or tie down points
- Always dry your soft shackle before storing for extended periods
- Your soft shackle is protected from sun degradation but should not be stored in direct sunlight for extended periods, extended exposure to sunlight will degrade the strength of your shackle
- Breaking strength is 13200kg
- As with snatch straps, the shackles breaking strength will decrease when wet
- Please keep bystanders at least 2 times the length of the recover strap away from the vehicles being recovered
- Not to be used as a lifting device